



Instruction Manual

使用説明書

Vertax Battery Grip E-11For Canon 5D Mark III









Name of each part (部件名稱)

- 1 Protective cover
- 2 Electrical contacts
- 3 Mounting Screw
- 4 Guide pin
- (5) Locking ring
- Battery magazine release handle 6
- 7 DC cord mount
- 8 AF point selection/Magnify Button
- AE lock/FE lock /Index/Reduce 9 button
- 10 AF start button
- 11) Multi selector Attachment wheel
- Vertical-grip operation switch (12)
- 13) Multi function button
- Shutter button 14)
- 15) Camera battery compartment cover slot
- (16) Main Dial
- 17) Hand strap mount
- Tripod socket 18)
- Battery Magazine BGM-E9L 19 (for LP-E6)
- 20 Battery pack compartment
- Battery Magazine BGM-E9A (for size-AA/LR6 batteries)

- 1 保護蓋
- 2 電子觸點
- 3 固定螺釘
- 4 定位銷
- (5) 裝卸旋鈕
- 6 電池倉鎖把手
- 直流電源綫插孔
- 7
- 8 自動對焦點選擇/放大按鈕
- 9 自動曝光鎖/閃光曝光鎖/ 索引/縮小按鈕
- 10 自動對焦啓動按鈕
- 11) 多重選擇器
- (12) 縱向位置操作開關
- 13) 多功能按鈕
- 14) 快門按鈕
- 相機電池倉蓋槽 15)
- 16) 主撥盤
- 17) 手提帶環
- 18) 三脚架接孔
- 電池夾BGM-E9L 19 (LP-E6用)
- 電池倉 20
- 電池夾BGM-E9A (AA/LR6尺寸電池用)




















Battery Grip Vertax Instructions

Thank you for purchasing a PIXEL product.

The Vertax is a battery grip that can hold 2pcs battery LP-E6 or 6pcs size AA/LR6 batteries. It is also equipped with a vertical-grip shutter button. Multi selector Attachment wheel, Main Dial, etc. to enable shooting in the same way as with horizontal grip.

Attach to the Camera

- 1. Remove the battery from the camera.(Fig.1-1)
- 2. Remove the camera battery compartment cover.(Fig.1-2)
- 3. Insert the detached cover into its storage slot to ensure that it will not be lost. (Fig.2)
 - When taking out the cover, press lightly on the cover hinge and pull it out upward at a slanted angle.
- 4. Remove the protection cover, and then insert the electrical contacts into the camera battery compartment (Fig.3-1)
- 5. Align the attachment screw with the camera's tripod socket, and then turn the attach/detach knob to tighten securely. (Fig.3-2)
- Do not further push open the battery compartment cover when it is already opened. Doing so may damage its hinge.
- Be sure to attach the battery grip to the camera before inserting the batteries. The results of the battery check may not be displayed properly if you attach the battery grip to the camera with the batteries already inside.
- Before moving the battery grip from the camera, be sure to turn the camera's power switch to (off), and take out the batteries. After removing the batteries, attach the protective cover to the electrical contacts.

Lithium Battery Installation

- 1. After flipping out the release handle, turn it as shown by the arrow, and then pull out the battery magazine (BGM-E9L). (Fig.4)
- 2. Insert one or two Battery LP-E6 into the battery magazine (for LP-E6). (Fig.5)
- 3. Attach the battery magazine into the battery grip. (Fig.6-1) After attaching, check that the battery magazine is securely attached to the battery grip.
- 4. Close the release handle. (Fig.6-2)
- If only one battery is used, it can be inserted in either the right or left side.
- If two battery packs are inserted, power is supplied simultaneously by both batteries. Two batteries with different charging levels can be inserted and used without any problems.
- Removing the battery packs or size AA/LR6 batteries from the battery grip when the camera will not be used for an extended period.

AA/LR6 Battery Installation

- 1. Insert the batteries into the Battery Magazine BGM-E9A (for Batteries). (Fig.7) Make sure the +and -battery contacts are properly oriented as shown in the figure
- 2. Attach the battery magazine into the battery grip. (Fig.8-1)
- 3. Close the release handle. (Fig.8-2)
- Less images can be shot when using size-AA/LR6 batteries. Also, the number of possible shots may vary depending on the batteries brand and storage conditions, so usage of size-AA/LR6 batteries is recommended only for emergencies.
- When using with non-rechargable size AA/LR6 batteries, please use when temperature is above 20°C. The camera may not work when used in low temperature or when old and new batteries are used together.

Using the Battery Grip

- 1. Turning the vertical-grip operation switch to (ON)(Fig.9)make the battery grip buttons and dial function in the same way as those on the camera.
- 2. When shooting in the horizontal-grip position, turn the vertical-grip operation switch to (OFF) so that you will not accidentally use the button or dial on the battery grip.
- The battery power level can be checked on the camera, such as the right Fig.

Battery info.	INFO. 14
₽LP-E6	65%
Shutter count	183
Recharge performance	000
DLP-E6	■ ■■ 66%
Shutter count	67
Recharge performance	000
	MENU 🗢

Specifications |

Battery:	1 or 2 of LP-E6 Battery, Or 6pcs AA/LR 6 Alkaline Battery
Power switch:	Camera's Power Switch
Working temperature:	0°C-+40°C
Working humidity:	85% Or Less
Dimensions:	Approx.153.1(W)x113.3(H)x85.7(D)mm
Weight:	Approx.279.4 g(without batteries and battery magazine)

The product specifications and exterior are subjected to change without notice.

This manual information is updated at 1st May, 2012. If you wish to use this product combined with other Pixel products published after this date; please consult with the PIXEL dealer for further information.

Now you can start to use incredible PIXEL product. If you have any question, please contact your local dealer or visit to http://www.pixelhk.com

電池盒兼手柄 E-11

使用説明書

感謝你購買品色産品。

E-11是一個可以裝兩個電池LP-E6或6個AA/LR6尺寸電池的電池盒兼手柄。本電 池手柄還配有縱向位置快門按鈕、多重選擇器、主撥盤等,使你在縱向拍攝時與橫向 拍攝時的操作方式相同。

在使用本産品之前,請務必仔細閱讀本使用説明書。

請務必妥善保管好本書,以便日後能隨時查閱。

請在充分理解内容的基礎上,正確使用。

安裝到相機

- 1.從相機中取出電池。(圖1-1)
- 2.卸下相機電池倉蓋。(圖1-2)
- 3. 將卸下的電池倉蓋插入存放區,以免丢失(圖2)。

當取出電池倉蓋時,請輕輕的按住電池倉蓋的轉軸,并以傾斜的角度向上將其拉出。

- 4.卸下保護蓋, 然後將電子觸點部插入相機電池倉。(圖3-1)
- 5.將固定螺釘與相機三脚架接孔對準,然後擰緊裝卸旋鈕。(圖3-2)
- 當電池倉蓋已打開時,請不要繼續推開倉蓋。這樣做可能會損壞電池倉蓋得轉 軸。
- 在插入電池之前, 請務必先將電池手柄安裝到相機上。如果您將已裝入電池的電 池手柄安裝到相機上,則相機可能無法正確地顯示電池電量檢測結果。
- 將電池手柄從相機上卸下之前,請務必先將相機的電源開關撥到(OFF)位置并取出 電池。取出電池後,請爲電子觸點安裝保護蓋。

安裝鋰電電池

- 1. 撥出電池倉鎖把手後,按照箭頭所示反向轉動,然後拉出電池夾 (BGM-E9L)。(圖4)
- 2.在電池夾(LP-E6用)中裝入單個或兩個電池 LP-E6。(圖5)
- 3.將電池夾裝入電池手柄。(圖6-1)
- 4.關閉電池倉鎖把手。(圖6-2)
- 如果衹使用單個電池,可將其裝在右側或左側。
- 如果安裝了兩個電池,則兩個電池同時供電。可裝入兩個電量不同的電池并且使 用起來不會有任何問題。
- 長時間不使用相機時,請從電池手柄中取出鋰電電池。

裝入AA/LR6尺寸電池

- 1.將電池裝入電池夾BGM-E9A(AA/LR6尺寸用)。(圖7) 按照圖示所示,確保電池的正負觸點朝向正確。
- 2.將電池夾裝入電池手柄。(圖8-1)
- 3.關閉電池倉鎖把手。(圖8-2)
- 使用AA/LR6尺寸電池時,能够拍攝的圖像較少。此外,根據電池的品牌和存放條 件,能够拍攝的圖像張數可能不同,因此建議您衹在緊急的情况下使用AA/LR6尺 寸雷池。
- ▶ 利用非充電式AA/LR6尺寸電池時,請在20℃以上的温度下使用6個相同品牌的新 電池。在低温條件下或新舊電池混合使用時,相機可能不工作。

使用電池手柄

- 1.將縱向位置操作開關轉到(ON)位置(圖9)以使 用電池手柄按鈕和撥盤功能與相機相應部分 的功能相同。
- 2.在進行横向位置拍攝時,請將縱向位置開關 轉到(OFF)位置,以免不小心使用電池手柄上 的按鈕或撥盤。
- 3.可以在相機上查看電池電量,如右圖。

立置操作開關轉到(ON)位置(圖9)以使 F柄按鈕和撥盤功能與相機相應部分 目同。 黄向位置拍攝時,請將縱向位置開關 FF)位置,以免不小心使用電池手柄上	電池資訊 企 LP-E6 快門釋放次數 電池充電效能	INFO EZ
けが正真、のえれがい。使用電池子樹上 投機盤。 目機上查看電池電量、如右圖。	○ LP-E6 快門釋放次數 電池充電效能	66% 67 000 MENU \$

规格

電源	(1)一個或兩個電池LP-E6 (2) 6 個AA/LR6尺寸碱性電池
電源開關	相機的電源開關
工作温度範圍	0°C−+40°C
工作濕度範圍	85%或更小
尺寸	約153.1(寬)x113.3(高)x85.7(厚)mm
重量	約279.4克(不含電池和電池夾的重量)

産品規格及外觀如有變化, 恕不另行通知。

本説明書中的信息更新至2012年05月01日,如果要與此日期之後發布的産品組合 使用,有關信息請向品色經銷商咨詢。

現在,你可以體驗無與倫比的品色產品。如有任何疑問可以向當地經銷商咨詢, 或登陸 http://www.pixelhk.com.cn查詢

制造商: 品色(香港)企業有限公司 地 址:香港九龍荔枝角青山道704號合興工業大厦4樓 電 話: (852) 2384-1188